



## コンベヤベルト 在庫サイズ一覧表

帆布	ベルト強カ /プライ数	ゴム厚	ベルト幅 (mm)																										
			100	125	150	200	250	300	350	400	450	500	550	600	700	750	800	900	1000	1050	1100	1200	1400	1500	1600	1800	2000		
普通耐摩	EP 100/1	1.5X1.5																											
	NN 100/2	1.5X1.5																											
	EP 125/2	3.0X1.5																											
	NN 125/2	3.0X1.5																											
	EP 125/3	3.0X1.5																											
	NN 125/3	3.0X1.5																											
	EP 160/2	3.0X1.5																											
	EP 160/3	3.0X1.5																											
	NN 160/3	3.0X1.5																											
	NN 160/4	3.0X1.5																											
	EP 250/2	5.0X1.5																											
	NN 250/3	5.0X1.5																											
	EP 250/3	5.0X1.5																											
	EP 315/3	5.0X1.5																											
	EP 315/4	5.0X1.5																											
	NN 315/4	5.0X1.5																											
	EP 315/3	6.5X2.5																											
	NN 315/4	6.5X2.5																											
	EP 400/3	5.0X1.5																											
	NN 400/4	5.0X1.5																											
NN 400/4	6.0X3.0																												
EP 400/4	6.0X3.0																												
EP 400/3	6.5X2.5																												
NN 400/4	6.5X2.5																												
EP 500/3	5.0X1.5																												
NN 500/4	5.0X1.5																												
EP 500/3	6.5X2.5																												
NN 500/4	6.0X3.0																												
EP 630/4	6.5X2.5																												
NN 630/5	6.0X3.0																												
EP 630/5	6.0X3.0																												
EP 800/4	6.5X2.5																												
NN 800/5	6.0X3.0																												
高張力片面	160/2	2.0X(1.0)																											
	250/3	2.0X(1.0)																											
マックスロン (耐衝撃性)	315/2	6.0X3.0																											
	500/2	6.0X3.0																											
ケークフリー	250/2	5.0X1.5																											
	315/3	5.0X1.5																											
ケーク バリヤー (付着防止)	250/2	5.0X1.5																											
	315/3	5.0X1.5																											
	315/3	6.5X2.5																											

耐油性	ベルト強カ /プライ数	ゴム厚	ベルト幅 (mm)																									
			100	125	150	200	250	300	350	400	450	500	600	750	800	900	1000	1050	1200	1400	1500							
重耐油 SOR	160/2	1.5X1.5																										
	160/2	3.0X1.5																										
	250/3	3.0X1.5																										
	250/3	5.0X1.5																										
	315/4	3.0X1.5																										
315/4	5.0X1.5																											

傾斜用	ベルト強カ /プライ数	ゴム厚	ベルト幅 (mm)																									
			50	65	75	90	100	125	150	200	250	300	350	400	450	500	600	700	750	800	900	1000	1050	1100	1200			
ラフトトップ	160/2	2.5X0																										
	160/2	2.5X1.0																										
ラフトトップ (白)	160/2	2.5X0																										
ラピスタン (MTトップ)	160/2	1.5X0																										

## 平ベルト 在庫サイズ一覧表

	プライ数	ベルト幅 (mm)																												
		20	25	30	38	50	63	75	90	100	115	125	150	175	200	250	300	350	400	450	500	600	700	750	800	900	1000	1200	1500	
ハーバー (JIS3種 相当品)	2P																													
	3P																													
	4P																													
	5P																													
	6P																													
ポート (JIS2種 相当品)	3P																													
	4P																													
	5P																													
	6P																													
	7P																													
8P																														
白生地	プライ数	ベルト幅 (mm)																												
		200	300	400	500	600	650	700	750	800	900	1000	1050	1200																
9Aホワイト	3P																													
TA帆布	3P																													

○ : 弊社在庫サイズ  
■ : メーカー標準品

傾斜用	ベルト強カ /プライ数	ゴム厚	ベルト幅 (mm)																									
			100	125	150	200	250	300	350	400	450	500	600	700	750	800	900	1000	1050									
中寄 (5R)	100/2	1.5X1.5																										
	125/2	3.0X1.5																										
	125/3	3.0X1.5																										
	160/3	3.0X1.5																										
	250/3	5.0X1.5																										
	315/4	3.0X1.5																										
315/4	5.0X1.5																											
中寄 耐油 (SOR5R)	160/2	3.0X1.5																										
	250/3	3.0X1.5																										
中寄 耐熱 (5R)	160/2	3.0X1.5																										
白色 中寄 (5R)	100/2	1.5X1.5																										

垂直 搬送用	ベルト強カ /プライ数
-----------	----------------